



SIMSON CLEANER E

PREPARATION AGENT

KEY BENEFITS

- Short drying time
- Cleaning
- Pre-treatment

DESCRIPTION

Simson Cleaner E is a preparation agent, ideally suitable for cleaning and degreasing substrates for bonding or sealing with specific Bostik SMP products. Consult the Technical Data Sheet of the particular product.

APPLICATION

- Cleaning and degreasing joints in teakwood decks (prior to the application of Simson Prep P).
- Removing uncured sealant and adhesive, based on Silyl Modified Polymer (SMP), silicones, polysulphide and polyurethane from substrates and tools.
- Degreasing and cleaning glass substrates.

METHOD OF USE

The substrates should be firmly rubbed with a clean, colourless cloth, wetted with Cleaner E. In case the substrate is strongly contaminated repeat this once more.

Note: It is recommended to carry out a trial in advance on a small piece, to check whether the substrate will be affected by Cleaner E.

Drying time: Pretreatment of teakwood decks: Prep P can be applied immediately. For other applications a drying time of 5 minutes is recommended.

COVERAGE

The coverage of Cleaner E on teakwood deck joints is approximately 15 m² per liter.

TECHNICAL DATA

CHARACTERISTIC		VALUE
Dry contents		0%
Flashpoint	[°C]	-4
Specific gravity	[g/ml]	0.9
Colour		Transparent
Packaging		500 ml tin

STORAGE STABILITY

Simson Cleaner E can be stored for 12 months in an original, unopened container in a dry place at temperatures between +5°C and +30°C.

FURTHER INFORMATION

The following publication is available on request:

- Material Safety Data Sheets (MSDS)

The information given and recommendations made herein are based on Bostik's research only and are not guaranteed to be accurate. The performance of the product, its shelf life, and application characteristics will depend on many variables, including the kind of materials to which the product will be applied, the environment in which the product is stored or applied, and the equipment used for application. Any change in any of these variables can affect the product's performance. It is the buyer's obligation, prior to using the product, to test the suitability of the product for an intended use under the conditions that will exist at the time of the intended use. Bostik does not warrant the product's suitability for any particular application. The product is sold pursuant to Bostik's Terms and Conditions of Sale that accompanies the product at the time of sale. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute permission, inducement, or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.

SMART HELP

Please contact your local representative

